



CAST IRON RADIATORS

Units 13-14 Charlwoods Road  
East Grinstead, West Sussex, RH19 2HU  
[www.clyderadiators.co.uk](http://www.clyderadiators.co.uk) 01342 305550

A brand of IRSAP, Italy's leading manufacturer of design led radiators.

EDS 669/12 21.10.21

# Contents

Clyde is a brand of the IRSAP; Italy’s leading manufacturer of design led radiators. With over 50 years experience, we have the expertise to produce the best in quality & customer service.

Clyde provides bespoke solutions for LSTs, Cast Iron, Multi Column and Aluminium radiators. With a wide range of traditional and contemporary radiators, Clyde's solution based approach is designed to ensure we supply the ideal solution for all commercial and industrial requirements.

Our dedicated team of technical advisors and estimators will discuss your installation including the calculation of your heat output requirements (from drawings if necessary), arrange a full quotation based on your exact project specifications and provide lead times. They can also arrange a site visit from our National Sales Network if required.

For more information about Clyde or any of our products, please contact our customer service department: 01342 305522 / 305566

Key Features & Technical Data	4-5
Selecting your FKR	6
Connections Configurations	7
Fixing & Handling	8-9
Assembling & Painting	10-11
Colour options & valves	12-14

The timeless styling of Clyde's Traditional range of FKR cast iron column radiators makes them equally appropriate for period property refurbishment or contemporary living spaces.

KEY FEATURES


- ▶ Closed column Hospital pattern sections
- ▶ 5 Heights
- ▶ 2, 4 and 6 column options
- ▶ Footed ends available for the 2 column, optional cast feet or wall brackets
- ▶ Protective primer coating (required paint finishing on site)



\* Subject to correct handling, installation, water treatment and operation, Clyde FKR radiators are guaranteed against manufacturing defects for 10 years from date of despatch.

PACKING, HANDLING AND SITE WORK

- ▶ With large orders radiator sections will be supplied on pallets to facilitate handling.
- ▶ Accessories are delivered packed separately for fitting by the installer. It is important that radiators are protected from the elements during offloading and are stored in dry and adequately heated premises. After radiators have been removed from their pallets, they must be kept vertical whilst being carried to their installation locations to avoid damage to the section joints.
- ▶ Radiators are factory assembled and pressure tested in blocks of up to 10 sections. For longer radiators additional blocks are supplied complete with nipples and joints for site assembling.
- ▶ Joining Keys are optionally available where additional blocks are supplied, the below outlines the required key;
  - ▶ All 6 column radiators require a Heavy Duty Key.
  - ▶ For 2, and 4 Column radiators;  
If more than two blocks are joined to make a complete radiator; Heavy Duty Key  
If there are 4 or more completed radiators to be made; Heavy Duty Key  
If there are 3 or less complete radiators to make & each completed radiator needs only 2 blocks to be joined; Basic Key



Footed ends available on the FKR 2 column range, please add 55mm to the overall height of your section.  
All footed end sections have FS at the end of the Model name.

TECHNICAL DATA

PRODUCT FEATURES

- ▶ Closed sections, 2, 4 or 6 column options
- ▶ 2 Floor & 1 Wall mounting option
- ▶ Protective primer coating (requires paint finishing on site)
- ▶ Also available in 25 RAL colours, 28 Special Finishes, Polished & Lacquer
- ▶ Max. operating pressure of 6 Bar
- ▶ Cast Iron material complying with ISO 185.




HEAT EMISSION RATES

- ▶ ΔtT50 (75°C / 65°C / 20°C)
- ▶ ΔtT55.5 (82°C / 71°C / 21°C)
- ▶ ΔtT60 (90°C / 70°C / 20°C)
- ▶ BS EN 442-1 conditions of ΔtT50

RANGE SELECTION

- ▶ 4 heights (mm); 280, 430, 580, 680
- ▶ 3 Column options; 2, 4 & 6
- ▶ Footed Ends in selected 2 column sizes

TECHNICAL DRAWINGS



Model	BS EN442 Emission rates				Max. no. sections ** (recommended)	Section Details						
	75/65/20°C Δt50 watts	Exponent	82/71/21°C Δt55.5 watts	90/70/20°C DT60 watts		overall length* L mm	overall height H mm	Bore centres B mm	Depth D mm	Dry Weight (Kg)	Water Content (Litres)	Surface Area (m <sup>2</sup> )
FKR6C28	71.6	1.3	82	90.8	30	60.5	280	200	250	4.8	0.88	0.185
FKR2C43	42.6	1.3	48.8	54	30	60.5	430	350	70	2.8	0.41	0.09
FKR2C43FS	42.6	1.3	48.8	54	30	60.5	430	350	70	2.2	0.41	0.09
FKR4C58	95.6	1.31	109.6	121.4	30	60.5	580	500	160	5.8	0.9	0.255
FKR2C68	62.3	1.3	71.4	79	30	60.5	680	600	70	3.75	0.45	0.142
FKR2C68FS	62.3	1.3	71.4	79	30	60.5	680	600	70	3.6	0.45	0.142
FKR2C98	86	1.3	98.5	109	30	60.5	980	900	70	5.12	0.8	0.205
FKR2C98FS	86	1.3	98.5	109	30	60.5	980	900	70	4.9	0.8	0.205

\* overall length = section length + joint ring

\*\* for maximum emission of 6kW at DT60 or 60 sections maximum

QUICK SIZING CHARTS

ΔtT50 (75°C / 65°C / 20°C) BC EN442-1:1995

Model	Watts per section	Radiator emission in kilowatts											
		0.6	0.8	1.0	1.25	1.5	1.75	2.0	2.5	3.0	4.0	5.0	6.0
		Nearest number of sections required											
FKR6C28	71.6	8	11	14	17	21	24	28	—	—	—	—	—
FKR2C43	42.6	14	19	23	29	—	—	—	—	—	—	—	—
FKR2C43FS	42.6	14	19	23	29	—	—	—	—	—	—	—	—
FKR4C58	95.6	6	8	10	13	16	18	21	26	—	—	—	—
FKR2C68	62.3	10	13	16	20	24	28	—	—	—	—	—	—
FKR2C68FS	62.3	10	13	16	20	24	28	—	—	—	—	—	—
FKR2C98	86	7	9	12	15	17	20	23	29	—	—	—	—
FKR2C98FS	86	7	9	12	15	17	20	23	29	—	—	—	—


ΔtT55.5 (82°C / 71°C / 21°C)

Model	Watts per section	Radiator emission in kilowatts											
		0.6	0.8	1.0	1.25	1.5	1.75	2.0	2.5	3.0	4.0	5.0	6.0
		Nearest number of sections required											
FKR6C28	82	7	10	12	15	18	21	24	30	—	—	—	—
FKR2C43	48.8	12	16	20	26	—	—	—	—	—	—	—	—
FKR2C43FS	48.8	12	16	20	26	—	—	—	—	—	—	—	—
FKR4C58	109.6	5	7	9	11	14	16	18	23	27	—	—	—
FKR2C68	71.4	8	11	14	18	21	25	28	—	—	—	—	—
FKR2C68FS	71.4	8	11	14	18	21	25	28	—	—	—	—	—
FKR2C98	98.5	6	8	10	13	15	18	20	25	30	—	—	—
FKR2C98FS	98.5	6	8	10	13	15	18	20	25	30	—	—	—

ΔtT60 (90°C / 70°C / 20°C)

Model	Watts per section	Radiator emission in kilowatts											
		0.6	0.8	1.0	1.25	1.5	1.75	2.0	2.5	3.0	4.0	5.0	6.0
		Nearest number of sections required											
FKR6C28	90.8	7	9	11	14	17	19	22	28	—	—	—	—
FKR2C43	54	11	15	19	23	28	—	—	—	—	—	—	—
FKR2C43FS	54	11	15	19	23	28	—	—	—	—	—	—	—
FKR4C58	121.4	5	7	8	10	12	14	16	21	25	—	—	—
FKR2C68	79	8	10	13	16	19	22	25	—	—	—	—	—
FKR2C68FS	79	8	10	13	16	19	22	25	—	—	—	—	—
FKR2C98	109	6	7	9	11	14	16	18	23	28	—	—	—
FKR2C98FS	109	6	7	9	11	14	16	18	23	28	—	—	—

PIPE CENTRES & TECHNICAL DRAWINGS



CONNECTIONS


All connection fittings, including joining nipples for site assembling of blocks, must be dry jointed using the joint rings supplied. Thread pastes or tapes with or without packing such as hemp **must not be used**. All machined faces and threads must be thoroughly cleaned before joining.

A set of connection fittings and joint rings is provided for each radiator.

- Each set comprises :
- 2 x R1¼ x R½ pipe connection bushes (or R1¼ x R¾ when requested)
  - 1 x R1¼ plug (LH thread)
  - 1 x R1¼ vent bush (RH thread) and R½ vent valve.


Radiators are normally installed with either BOE (bottom opposite end) or TBOE (top & bottom opposite end) connections. For installations with BOE connections,

The vent valve should always be fitted at the outlet end of the radiator. If necessary, rotate the radiator to position the vent correctly.



BOXING AND ENCLOSURES

It is recommended that radiators are installed with a minimum gap of 70mm above floor level. A full width window sill above the radiator extending the depth of the radiator will reduce emission rates by approximately 4%. Boxing of radiators or the use of decorative enclosures will reduce emission rates by upwards of 15%, according to the design of the boxing. Any restriction of the free flow of air over the radiator surface is detrimental to convected heat emission. Obscuring the front surface of the radiator eliminates the beneficial effect of radiated heat.



COMMISSIONING

In accordance with Part L1 2006 of the Building Regulations and BS7593:1992 code of practice for the treatment of hot water and central heating systems, we strongly recommend flushing the heating system post installation of new radiators and then adding the correct quantity and type of inhibitor for use with your radiator and system to prevent corrosion. Damage caused to systems not protected by a suitable inhibitor will not be covered by manufacturer’s guarantee

Before unpacking, please ensure that the delivered sizes and quantity are correct. Any shortages or damages must be notified to Clyde Radiators in writing within 7 days; Clyde Radiators, 13-14 Charlwoods Road, East Grinstead, West Sussex, RH19 2HU


► **FIXING ARRANGEMENTS, FLOOR MOUNTS & WALL BRACKETS**

**FKR radiators are quoted with footed end sections in selected sizes, if you require an alternative mounting option please specify at time of order.** Clyde also offer alternative mounting options; cast feet and wall brackets, wall ties come as standard with all mounting options. Floor mounting is recommended for cast iron radiators. Wall brackets may be used for some radiators if the wall is sound and capable of taking the weight of the radiator. If the wall is generally unsound, built of low density cellular blocks or is a timber stud wall, floor mounts with wall stays should be used. Special arrangement may be necessary for providing fixing for stud walling, dry lined and composite walls (eg flint aggregate) which are commonly encountered in period restoration projects.


All screw fixes and wall plugs must be appropriate fittings selected to be suitable for the fabric of the wall to which the supports or brackets are being fixed. Do not use fibre or ceramic plug materials as these degrade in time and become unreliable. Advice on screw fixes and wall plugs is provided by specialist suppliers such as Fischer or Rawlplug. Pipework should never be used to provide support for the radiator. Assembling instructions are supplied with all Clyde radiators.

► **BLOCK MAKE-UP FOR ALL RADIATORS**

8	F 6	F
↓	F N-2 intermediate sections F	
20	F 18	F
21	F 9	F 9 F
22	F 6	F 6 F 6 F
23	F 10	F 10 F
24	F 7	F 6 F 7 F
25	F 11	F 11 F
26	F 7	F 8 F 7 F
27	F 12	F 12 F
28	F 8	F 8 F 8 F
29	F 13	F 13 F
30	F 9	F 8 F 9 F
31	F 14	F 14 F
32	F 9	F 10 F 9 F
33	F 15	F 15 F
34	F 10	F 10 F 10 F
35	F 16	F 16 F
36	F 11	F 10 F 11 F
37	F 17	F 17 F
38	F 11	F 12 F 11 F
39	F 18	F 18 F
40	F 12	F 12 F 12 F




► **MOUNTING OPTIONS**




Please specify you chosen mounting option at time of order.

► **CONNECTIONS**

Radiator blocks have Rp1¼ right hand threads at one end and Rp1¼ left hand threads at the other. Lay the blocks out so the right hand threads are aligned with left hand threads to suit the threaded nipples - refer diagram below. Before joining, inspect all blocks for primer paint runs and arrange these to be at the bottom of the radiator. Paint runs can usually be removed with a stiff wire brush. Match all blocks so that the assembled radiator is uniform along its entire length.




► **BLOCK ASSEMBLING**



► **HANDLING**

- With large orders, radiator sections will be supplied on pallets to facilitate handling.
- Accessories are delivered packed separately for fitting by the installer. It is important that radiators are protected from the elements during offloading and are stored in dry and adequately heated premises. After radiators have been removed from their pallets, they must be kept vertical whilst being carried to their installation locations to avoid damage to the section joints.
- Radiators are factory assembled and pressure tested up to ten sections. For longer radiators additional blocks are supplied complete with nipples and joints for site assembling.
- Assembling tools are optionally available where additional blocks are supplied.
- Joining Keys are optionally supplied on a sale or return basis where additional blocks are supplied.

Cast iron radiators are heavy. Always provide sufficient manpower to make carrying safe. Incorrect handling of radiator blocks can cause water leaks from section joints. Lift the radiator blocks in the centre to bring them to the vertical position before lifting and carrying. Never carry radiators in a stretcher fashion.





► ASSEMBLING

Sections are joined with dry fitted joining gaskets between the machined faces of each section. Bushes and plugs are dry sealed in the connections at each end of the radiator with a joining gasket supplied as part of the bush or plug. Hemp, tape or sealing compounds **must not be used**.

- Position the section block horizontally on two lengths of timber.
- Ensure that the machined faces and threads of the section are perfectly clean.
- Screw two nipples one full turn into each of the section tappings. Note that the nipples have left and right handed threads.
- Place a joining gasket (as supplied) on each nipple.
- Clean the machined surfaces and threads of the adjoining block or section. Lay this block or section beside the first block ensuring that the threads mating to the nipples have the correct thread rotation.
- Measure and mark off the length of the adjoining block or section on the nipple turning bars.
- Insert the turning bars through the nippleways of the adjoining block or section to engage with the nipples.
- Rotate both nipple turning bars equally to draw the blocks together keeping them parallel. If the blocks are not pulled together evenly, threads can be damaged and may give rise to leakage. Tighten the section nipples to tommy bar.
- Repeat operations 2 to 8 until the radiator is fully assembled.
- Fit bushes, blanking plug and vent valve according to the connection plan required.

Please visit our youtube channel where you can watch a demonstration on how to join and assemble a sectional cast iron radiator.

<https://www.youtube.com/watch?v=Nu1RJQGSrKk&list=PLMGnLO7Af-x6fIWFeVMOLKwq-5OXBVaRc>

► PAINTING

CHOICE OF PAINT

FKR radiator blocks are supplied with a protective primer coating that will afford limited protection against the formation of rust provided that the blocks are correctly dry stored. Blocks will rust if they become wet.

**Clyde Radiators can deliver your cast iron radiators fully furnished and ready for installation. We use a robust, polyester powder coat paint, which is applied by our specialist painters based in the UK, to achieve a long lasting, durable finish. Please be aware that as a result of the casting process, cast iron radiators have a rough surface finish with small imperfections which will show after the painting process.**

THIS PROTECTIVE PRIMER COATING IS NOT INTENDED AS AN UNDERCOAT.

For a superior, long lasting paint finish we recommend that a protective coat of a zinc based rust inhibitor is applied. This must be compatible with the undercoat and finish coat selected for the radiator. Radiators may be finished with most domestic paints that are formulated to withstand temperatures up to 100°C. Spray paints (air drying or oven cured) as used for car bodywork are also suitable. Paint supplier’s recommendations regarding the use of an undercoat should be observed to ensure a true colour rendering.

**Topcoats and undercoats MUST NEVER be WATER BASED or EMULSION type.** Care must be taken in selecting undercoats as many modern formulations are water based although they are designed for use with oil based topcoats. A water based paint will always create rust pocks that will grow and become unsightly.

PAINTING

Paint may be applied by brush or spray and an undercoat should be applied, in accordance with the paint manufacturer’s instructions. The quantity of paint required may be calculated from the coverage factor declared by the paint manufacturer and the surface area of the radiator sections.

Mount the radiators in their final positions and complete all pipe connections. Painting radiators ‘in situ’ against a wall is not recommended as the entire surface cannot be reached and there will be a high risk of rust formation on untreated surfaces.

When all installation work has been completed, disconnect the pipework and remove the radiators from the wall. Because the radiators are heavy and cumbersome to move, it is highly advisable to paint each radiator close to where it is being installed. Stand or lay the radiators on wood chocks. For safety, radiators must be supported whilst standing up, but it is necessary to turn them over to examine and treat all surfaces.

Using dry cloths, a wire brush and/or emery sheets, remove all dust and debris from the radiator surface. If any rust spots are found these must be removed and then treated with a chemical rust cleaner such as ‘Jenolite’.

FKR COLOUR OPTIONS - RAL COLOURS

If you are looking to have your FKR radiator in an alternative colour we offer the following RAL colour options, please specify chosen colour at time of order.



RAL 1001 - Beige



RAL 1013 - Oyster white



RAL 1015 - Light ivory



RAL 1019 - Grey beige



RAL 3000 - Flame red



RAL 3003 - Ruby red



RAL 3004 - Purple red



RAL 4003 - Heather violet



RAL 5024 - Pastel blue



RAL 6006 - Grey olive



RAL 6013 - Reed green



RAL 7016 - Anthracite grey



RAL 7032 - Pebble grey



RAL 7035 - Light grey



RAL 7040 - Window grey



RAL 7042 - Traffic grey A



RAL 7044 - Silk grey



RAL 8011 - Nut brown



RAL 8025 - Pale brown



RAL 9001 - Cream



RAL 9004 - Signal black



RAL 9005 - Jet black



RAL 9006 - White aluminium



RAL 9007 - Grey aluminium




RAL 9010 - Pure white


To discuss a quotation for other colours outside of the above range please call 01342 305550

FKR COLOUR OPTIONS - SPECIAL FINISHES


Choose from 28 Special finishes; Textured, Mottled, Metallics and Golds, please specify chosen colour at time of order.




Matt White




Sienna Brown




Carbon




Matt Black




Textured White




Textured Ivory




Textured Stone




Textured Matt Black




Mottled Silver




Mottled Bronze




Mottled Copper




Pearl White




Quartz




Sand




Sahara




Sunstone




Ancient Bronze




Satinato




Pearl Grey




Platinum




Metallic Grey




Grey Sparkle




Titanium Grey




Gun Metal Grey




Azurite



Black Sparkle



Nebula



Grey Skies

POLISHED AND LACQUERED

POLISHED

The FKR is also available in a beautiful polished finish. Created by hand in the UK, an initial black paint is used to protect hidden, hard to access areas of the radiator and to highlight the visible polished areas (the front, sides and tops of the sections are polished whilst the rear and more difficult access areas between the sections remain black); a series of polished processes produces the final stunning results.

LACQUERED

This industrial bare metal finish is hand finished so every radiator is unique, variations in colour, welding and burnishing marks differ from one section to another and add to the idiosyncrasy of each radiator.

# VALVES

Choose one of our TRV's to complement your cast iron radiator.

## ESTATE TRV

- Height of Wheelhead 127mm
- Available in Brass & Chrome
- Straight or Angled
- For angled valves allow an extra 80mm in total
- Estate TRV's are not Bi-directional
- Supplied in pairs of one thermostatic valve & one lockshield
- R½ x 15mm compression angled valves



## TRADITIONAL TRV

- Height of Wheelhead 115mm
- Chrome and Nickel finishes supplied with a Black top
- Antique Copper, Antique Brass and Polished Brass supplied with a Walnut top
- For angled valve allow an extra 90mm in total
- Traditional TRV's are not Bi-directional
- Supplied in pairs of one thermostatic valve & one lockshield
- R½ x 15mm compression angled valves



## TRADITIONAL XL TRV

- Height of Wheelhead 160mm
- Available in Chrome, Nickel & Antique Brass supplied with a Black top
- Available in Antique Copper & Polished Brass supplied with a Walnut top
- For angled valve allow an extra 120mm in total
- Traditional XL TRV's are not Bi-directional
- Supplied in pairs of one thermostatic valve & one lockshield
- R½ x 15mm compression angled valves



# OTHER CLYDE PRODUCTS

## Clyde Radiators

### COMMERCIAL HEATING SOLUTIONS

- 6 Flat Panel radiators
- Lightweight & Efficient Sectional Aluminum
- Sectional Cast Iron in 3 other styles
- 2 Bespoke LST options, made to specification
- Sectional Steel Multi Column in over 3200 sizes
- Radiant Panels
- Trench: Practical aluminium convector for underfloor heating
- Mini: Aluminium and copper convector, in steel casing with aluminium grille



[www.clyderadiators.co.uk](http://www.clyderadiators.co.uk)